


6x19 ÂME TEXTILE




Câble d'usage général
(treuil manuel, élingue...)

Diamètre (mm)	Diamètre fil (mm)	Section (mm ²)	Poids (kg / m)	CRM* 1.770 N/mm ²	CRM* 1.960 N/mm ²
3	0,20	-	0,03	4,9	5,4
4	0,25	-	0,06	8,7	9,6
5	0,33	-	0,09	13,6	15,1
6	0,39	14	0,12	21,0	23,0
7	0,45	18	0,16	28,0	31,0
8	0,52	24	0,22	37,0	41,0
9	0,58	30	0,27	46,0	51,0
10	0,64	37	0,33	56,0	63,0
11	0,72	47	0,41	71,0	79,0
12	0,78	55	0,49	84,0	93,0
13	0,84	64	0,57	97,0	108,0
14	0,90	73	0,65	111,0	124,0
15	0,96	83	0,74	127,0	141,0
16	1,04	98	0,87	149,0	165,0
17	1,10	109	0,97	166,0	185,0
18	1,16	122	1,08	185,0	206,0
19	1,22	135	1,19	205,0	227,0
20	1,28	148	1,32	225,0	251,0
21	1,36	167	1,48	254,0	282,0
22	1,42	183	1,62	277,0	308,0

* CRM : charge de rupture minimum

7x19 ÂME MÉTALLIQUE






Câble d'usage général
et de haubannage

Diamètre (mm)	Diamètre fil (mm)	Section (mm ²)	Poids (kg / m)	CRM* 1.770 N/mm ²	CRM* 1.960 N/mm ²
6	0,39	16	0,14	24	26
7	0,45	22	0,19	32	35
8	0,52	29	0,25	42	46
9	0,58	36	0,31	52	58
10	0,64	44	0,38	64	71
11	0,72	55	0,47	80	89
12	0,78	65	0,55	94	104
13	0,84	75	0,64	109	121
14	0,90	87	0,74	126	139
15	0,96	99	0,85	143	159
16	1,04	116	0,99	167	186
17	1,10	129	1,10	187	208
18	1,16	144	1,23	209	232
19	1,22	160	1,36	231	257
20	1,28	176	1,50	255	283
21	1,36	197	1,68	286	317
22	1,42	216	1,84	312	347
23	1,48	234	2,00	339	377
24	1,56	259	2,21	376	417
25	1,62	280	2,39	406	450
26	1,68	301	2,57	436	484

* CRM : charge de rupture minimum

CÂBLE GAINÉ

Diamètre intérieur (mm)	Diamètre extérieur (mm)	Construction	Poids (kg % m ca.)	CRM* 1.770/mm ²
2,0	3,0	5 x 7 + 1 TWK/FC	2,0	2,75
2,5	3,5	6 x 7 + 1 TWK/FC	3,0	3,67
3,0	4,0	6 x 7 + 1 TWK/FC	4,0	5,29
3,0	4,5	6 x 7 + 1 TWK/FC	4,5	5,29
3,0	5,0	6 x 7 + 1 TWK/FC	5,0	5,29
4,0	6,0	6 x 7 + 1 TWK/FC	8,0	9,41
4,0	6,0	6 x 19 + 1 TWK/FC	7,5	8,70
5,0	7,0	6 x 7 + 1 TWK/FC	11,5	14,70
5,0	7,0	6 x 19 + 1 TWK/FC	9,8	13,60
6,0	8,0	6 x 7 + 1 TWK/FC	18,0	21,10
6,0	8,0	6 x 19 + 1 TWK/FC	15,8	19,60
8,0	10,0	6 x 19 + 1 TWK/FC	25,4	34,80
10,0	12,0	6 x 19 + 1 TWK/FC	42,0	54,40
10,0	12,0	6 x 37 + 1 TWK/FC	40,0	52,20
12,0	14,0	6 x 19 + 1 TWK/FC	56,0	78,30
12,0	14,0	6 x 37 + 1 TWK/FC	59,0	75,10
14,0	16,0	6 x 19 + 1 TWK/FC	75,0	107,00
14,0	16,0	6 x 37 + 1 TWK/FC	77,0	102,00



Existe en différentes couleurs : blanc, transparent, rouge, noir, vert
Disponible également en câble inox.