


6x36 - ÂME TEXTILE

Câble de levage, élingue...

Diamètre (mm)	Diamètre fil (mm)	Section (mm²)	Poids 100m (kg)	CRM* 1.770 N/mm²
8	0,24	37,4	41,4	45,5
10	0,38	58,4	64,7	71,2
12	0,55	84,1	93,1	102,0
14	0,75	114,0	127,0	140,0
16	0,97	149,0	166,0	183,0
18	1,23	189,0	209,0	230,0
20	1,52	234,0	259,0	285,0
22	1,84	283,0	313,0	344,0
24	2,19	336,0	372,0	409,0
26	2,57	395,0	437,0	481,0
28	2,98	458,0	507,0	558,0
30	3,42	525,0	582,0	640,0
32	3,89	598,0	662,0	728,0
34	4,40	675,0	747,0	822,0
36	4,93	757,0	838,0	922,0
38	5,49	843,0	934,0	1.027,0
40	6,08	934,0	1.034,0	1.137,0

* CRM : charge de rupture minimum




6x36 WS - ÂME MÉTALLIQUE

Câble de levage, élingue...

Diamètre (mm)	Diamètre fil (mm)	Section (mm²)	Poids 100 m (kg)	CRM* 1.770 N/mm²
8	0,27	40,4	44,7	49,1
10	0,42	63,1	69,8	76,8
12	0,60	90,8	101,0	111,0
14	0,82	124,0	137,0	151,0
16	1,07	161,0	179,0	197,0
18	1,36	204,0	226,0	249,0
20	1,67	252,0	279,0	307,0
22	2,02	305,0	338,0	372,0
24	2,41	363,0	402,0	442,0
26	2,83	426,0	472,0	519,0
28	3,28	494,0	547,0	602,0
30	3,76	568,0	628,0	691,0
32	4,28	646,0	715,0	787,0
34	4,83	729,0	807,0	888,0
36	5,42	817,0	905,0	996,0
38	6,04	911,0	1.008,0	1.109,0
40	6,69	1.009,0	1.117,0	1.229,0
42	7,38	1.112,0	1.232,0	1.355,0
44	8,10	1.221,0	1.352,0	1.487,0
46	8,85	1.334,0	1.478,0	1.626,0
48	9,64	1.453,0	1.609,0	1.770,0
50	10,50	1.576,0	1.746,0	1.921,0
52	11,30	1.705,0	1.888,0	2.076,0
54	12,20	1.839,0	2.036,0	2.240,0
56	13,10	1.978,0	2.190,0	2.409,0
58	14,10	2.121,0	2.349,0	2.583,0
60	15,10	2.270,0	2.514,0	2.765,0
62	16,10	2.424,0	2.684,0	2.952,0
64	17,10	2.583,0	2.860,0	3.146,0
66	18,20	2.747,0	3.042,0	3.346,0
68	19,30	2.916,0	3.229,0	3.552,0


* CRM : charge de rupture minimum




EUROPACK 6

Diamètre (mm)	Diamètre (mm)	Section (mm ²)	Poids (kg / m)	CRM* 1.970 N/mm ²	CRM* 2.160 N/mm ²
6 x K19 S + IWRC	10	52	0,44	88	97
	11	64	0,54	107	118
	12	75	0,64	126	139
	13	89	0,76	150	165
6 x K26 WS + IRWC	14	103	0,87	169	186
	15	116	0,98	191	210
	16	133	1,12	219	231
	17	152	1,29	251	276
	18	168	1,42	277	305
	19	189	1,60	311	342
	20	209	1,77	345	380
6 x K31 WS + IRWC	22	254	2,15	419	461
	24	306	2,59	504	554
	26	363	3,08	598	658
	28	414	3,50	682	750
6 x K36 WS + IRWC	30	477	4,05	786	865
	32	541	4,59	891	980
	34	614	5,21	1.012	1.113
	36	687	5,83	1.132	1.245
	38	765	6,50	1.261	1.387
	40	850	7,22	1.402	1.542
	42	928	7,88	1.530	1.683
	44	1.032	8,77	1.701	1.871
	46	1.121	9,52	1.847	2.032
	48	1.221	10,37	2.012	2.213
	50	1.322	11,23	2.179	2.397
	52	1.434	12,18	2.364	2.600


* CRM : charge de rupture minimum




6 x K19



6 x K26



6 x K31



6 x K36

Applications :

- Câble de levage nécessitant une charge de rupture supérieure au 6x36 standard
- Fabrication d'élingues avec une CMU plus importante
- Très haute résistance à l'abrasion